

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

Claims 1-14 (canceled).

15. (previously amended) A cutting tool assembly, said assembly comprising:
a retainer sleeve including at least one radially outward projecting dimple;
wherein said retainer has a cylindrical circumference and a thickness dimension,
the amount of radial projection of said dimple beyond the cylindrical surface of the retainer is about 15-30 percent of the thickness dimension of said retainer.

16. A cutting tool assembly according to claim 15, wherein said retainer sleeve includes a plurality of said dimples spaced relative to one another about the circumference of said retainer sleeve.

17. A cutting tool assembly according to claim 15, wherein said dimples are generally semi-spherical.

Claims 18-28 (canceled).

29. (previously amended) A retainer, said retainer comprising:
a retainer sleeve including at least one radially outward projecting dimple;
wherein said retainer has a cylindrical circumference and a thickness dimension,
the amount of radial projection of said dimple beyond the cylindrical surface of the retainer is about 15-30 percent of the thickness dimension of said retainer.

30. A retainer according to claim 29, wherein said retainer sleeve includes a plurality of said dimples equally spaced relative to one another about the circumference of said retainer sleeve.

31. (canceled).

32. (currently amended) A cutting tool assembly according to claim 15 wherein said dimples extend between about .007 -.020[0] inches beyond an exterior cylindrical surface of said retainer.

33. (previously added) A cutting tool assembly according to claim 17 wherein said dimple has a diameter of between about .06-.10 inches.

34. (previously added) A cutting tool assembly according to claim 17 wherein said retainer has a plurality of said dimples.

35. (previously added) A cutting tool assembly according to claim 17 further comprising:

a bit holder, and

a cutter bit having a shank,

wherein said retainer is connected to said shank, and said cutter bit and retainer are inserted in a bore formed in said bit holder.

36. (currently amended) A retainer according to claim 29 wherein said dimples extend between about .007 -.020[0] inches beyond an exterior cylindrical surface of said retainer.

37. (previously added) A retainer according to claim 29 wherein said dimple has a diameter of between about .06-.10 inches.

38. (previously added) A retainer according to claim 29 wherein said retainer has a plurality of said dimples.

39. (previously added) A cutting tool assembly, said assembly comprising:

a retainer sleeve including at least one radially outward protruding surface; wherein said retainer has a cylindrical circumference and a thickness dimension,

the amount of radial projection of said protruding surface beyond the cylindrical surface of the retainer is about 15-30 percent of the thickness dimension of said retainer.

40. (previously added) A retainer, said retainer comprising:
a retainer sleeve including at least one radially outward protruding surface;
wherein said retainer has a cylindrical circumference and a thickness
dimension,

the amount of radial projection of said protruding surface beyond the
cylindrical surface of the retainer is about 15-30 percent of the thickness dimension of said
retainer.

41. (canceled).

42. (canceled).

3
B

43. (new) A generally cylindrical retainer, said retainer comprising:
a retainer sleeve including at least two radially outward projecting dimples;
wherein said retainer has a central longitudinal axis and a thickness dimension,
and all said at least two dimples are generally located within a common radial plane,
the amount of radial projection of said dimple beyond the cylindrical surface
of the retainer is about 15-30 percent of the thickness dimension of said retainer,
wherein said retainer is constructed from steel.

44. (new) A retainer according to claim 43 wherein said at least two
dimples extend between about .007 -.020 inches beyond an exterior cylindrical surface of
said retainer.

45. (new) A retainer according to claim 44 wherein said dimple has a
diameter of between about .06-.10 inches.

46. (new) A retainer according to claim 29 wherein said retainer has an
endface, and a bottom end, wherein a slit extends from said bottom end to said endface.

47. (new) A retainer according to claim 40 wherein said retainer has an
endface, and a bottom end, wherein a slit extends from said bottom end to said endface.
